

Distinctive by design.





Advanced performance. Minimalist design.

The T1 is the ideal solution for busy workplaces where space may be at a premium. With advanced dispensing features packaged in a minimal and contemporary design, the T1 will complement even the smallest communal area or kitchenette.



Distinctive by design.



High-capacity dispensing

The T1 eliminates the need for single-use plastic bottles with high-capacity dispensing. It delivers 50 litres per hour of chilled, ambient, and sparkling drinking water, making refilling reusable vessels such as drinking bottles fast and convenient.

Countertop convenience

This integrated tap system can be positioned over a sink or combined with a stylish circular drip tray which complements the design of the tap. The drip tray can either be plumbed into mains waste or used with the Borg & Overström alarmed waste kit.

Cutting-edge UV protection

As an option, the T1 can be pre-fitted with Viovandt®, a mercury-free, chemical-free and energy-efficient LED-UV water purification system. For complete peace of mind, it also includes additional hygiene features via Borg & Overström's Totality® methodology.

Minimal yet durable design

Beneath the minimalist, contemporary exterior lies an innovative water dispensing system built for durability and efficiency. The tap is PVD coated for a high-end yet durable finish, while the undercounter cabinet is colour-coated GreenCoat® steel.

Next-generation ProCore™

Under the counter is a compact powerhouse. ProCore™ is a low-maintenance next-generation water dispensing system. In addition to being energy-efficient, it's fitted with the new eco R290 refrigerant gas.

Low energy consumption

The T1 is consistently energy efficient, making it both economical and eco-friendly. This dynamic integrated tap system is lean and economical, with absolutely no sacrifice to output and quality.

Plug and play installation

There are no fiddly wires to connect with the T1. The plug and play USB 3 connector makes this tap super easy to install.

Ventilation kit included

A ventilation kit is included with this system. It's easy to install and increases the efficiency of the $ProCore^{TM}$ by allowing a continuous cycle of cool air.



Distinctive by design.



borg& overström Distinctive by design. Water system Configurations Water options 1 Ambient Sparkling Tap finishes Steel borgandoverstrom.com

Totality® - Hygiene-assured refreshment



Totality® is our assurance that water dispensed from a Borg & Overström water dispenser is as safe as it is refreshing. Water dispensers with a six-star Totality® rating deliver an exceptionally high standard of hygiene.



Digital precision
The discreet digital touch
panel has an antimicrobial
coating for a reassuringly
clean experience. Chilled,
sparkling, or ambient water
can also be dispensed touchfree via the Bluetooth® app.



Advanced UV-led protection.
As an option, the T1 can be fitted with Viovandt®, a mercury-free, chemical-free and energy-efficient LED-UV water purification system.
For complete peace of mind, it also includes additional hygiene features via Borg & Overström's Totality® methodology.



Sealed drinking water system. Dry Chill® is the most hygienic cooling process. No water is stored within the system, which greatly reduces the opportunity for bacteria to become established. Dry Chill® also produces a larger volume of lower temperature water due to its faster recovery time.



Independently certified anti-microbial, antipathogen sanitising procedure.
All dispensers are sterilised using Sterizen® sanitising infusion. No other brand of watercooler goes through this process, which is why only Borg & Overström appliances are laboratory certified to be 99.999% bacteria reduced.



High-performing, easy to fit carbon filters.

3M carbon filters provide the highest level of water hygiene security for your dispenser over a longer period of time.

All Borg & Overström water dispensers can be fitted with 3M carbon filters.


Distinctive by design.



borgandoverstrom.com

Specifications	T1 ProCore	Dispense options	Max power consumption	Steel	Black	Steel ECO-UV	Black ECO-UV
Tap dimensions	Power requirements Hertz 50/Volts 230-240	Chilled & Ambient	140W	741010	741000	741030	741020
W42xD163xH385mm		Chilled & Sparkling	200W	741050	741040	741070	741060
Dispense height 310mm	Water system Dry Chill®	Chilled, Sparkling & Ambient	200W	741090	741080	741110	741100
ProCore™ dimensions W320xD375xH335mm	Chilled temperature Min 2°C/Max 11°C						
Simple-fit Ventilation Base	Throughput flow rate						

Easy-to-fit ventilation kit



Distinctive by design.



W322xD431xH60mm

(Includes 20mm overhang)

50 litres per hour (LPH)

60 500ml bottles per hour (BPH)

Additions for T1



Biodegradable paper cups Environmentally-friendly disposable cups designed to fit Borg & Overström cup dispensers perfectly.



Install kit with 3M filter

a 3M filter.

Install appliances simply and

applications. Complete with

Alarmed waste kit Featuring an audible highwater level alarm to prevent the effectively in a wide range of waste tank from overflowing.



Personal drinking bottles 500ml capacity in black. Comes with quick-release leak-proof cap and carry strap.



500/750ml glass bottles Suitable for dishwashers and bottlewashers. Both sizes are a perfect fit for the T1 tap. Stylish swing-top lid.



Deep Sparkle® CO² refills Can be disposed via standard steel recycling or general waste. Requires CO² regulator with gauge.



Sanitisation kit Six monthly sanitising cycles ensure appliances function at the optimum hygiene levels.



T1 Drip tray The T1 drip tray is available in a steel and black finish. It can either be plumbed into mains waste or used with the alarmed waste kit.



Water refill station The refill station comes complete with a lockable spacious storage area. This heavy duty cabinet is constructed from black coated steel with a stainless steel top.



Distinctive by design.



Book a personal demonstration of the T1

Talk to an adviser +44 (0) 1362 695 006 sales@borgandoverstrom.com

Version: T1.EN.v010422 (EN borgandoverstrom.com